

world leaders in the art of linear measurement



SI3500

AMETEK
ULTRA PRECISION TECHNOLOGIES

Datasheet
502785
Issue 4
EDCR

New Orbit instrument for interfacing to Solartron Metrology Transducers



Features

- ▶ 2 orbit digital sensor inputs
- ▶ Simple Menu System
- ▶ 1 or 2 channel display (*user selectable*)
- ▶ 7 Digit Colour Display (*user selectable*)
- ▶ Analogue display with auto course/fine resolution
- ▶ Auto display colour change for in/out range
- ▶ Peak hold facility
- ▶ Data logging facility with up to 10,000 readings
- ▶ Discrete I/O
- ▶ 4-20ma or DC voltage output
- ▶ RS232 output
- ▶ Front panel IP65 protection

Description

The New SI3500 Orbit Controller is an instrument specifically designed to operate with Solartron's transducers operating on the 'Orbit' network, this plug and play instrument features an intuitive, menu-driven colour display which can be programmed to set limits and to record other parameters intuitively.

Powered from a 24 Vdc source, the SI3500 can be used to display one or two transducer readings, computed results from two transducers such as A, B, A+B, A-B, (A+B)/2, (A-B)/2, and computations with constants, for example angle measurements.

Full set up is made via the IP65 protected front keypad that can, if required, be password protected. The SI3500 also features discrete inputs/ outputs and a selection of analogue outputs in the form of 4-20mA or DC voltage.









Technical Specification

Product type	SI3500 - Orbit Digital
Display type	Colour LCD display 40Hz update rate with 30° Viewing Angle
Display length (mm) Display length (inches)	XX.XXXXX X.XXXXXX
Resolution (µm)	Down to 0.05 µm or 0.000005"
Analogue Display	Solid bar vertical or two horizontal bars (2axis)
Inputs	
Signal Input	Orbit (2 inputs)
Number of Orbit modules supported	Two directly plugged into the SI3500
Keypad	Membrane keypad with 9 keys: Print, Zero, Up, Down, Left, Right, Enter, peak/track, menu.
External input/output	
Serial	RS232 serial port (for printer or PC).
Discrete Output	six isolated discrete outputs (Channel A, Lo, OK, HI), (Channel B, Lo, OK, HI)
Analogue Output	2 Channels either configured 4-20mA or DC Voltage
Measurement configurations	
Data Logging	Store 10,000 readings by: external switch contact or preset time interval 1ms - 24 hours, displays Mean and Standard Deviation
Number of probes	Individual probe, Probe pair
Measurement type	A, B, A+B, A-B, (A+B)/2, (A-B)/2, (B-A/a), X and Y
Indications	Measurement Mode, Type of measurement, Lower and Upper Limited, DP Out of Range, measurement out of Limits
Electrical	
Power supply (VDC)	+24 VDC ± 10%
Mechanical and Enviromental	
Mounting	Bench Top or Panel options
Sealing	Front Panel IP65, Case IP51, Rear Connectors IP51
Mass	1.1kg
Temperature	Operating temperature from 0°C to +50°C storage between -20 C to +85°C
EMC	Immunity:EN6100-6-2:2001, Emissions: EN61000-6-3:2001
Dimensions	W x H x D(mm): 134 x 65 x 160 excluding bezel W x H x D(mm): 144 x 74 x 175 including bezel

Part Number	
Base Unit	911359

Also Available at Solartron Metrology



Solartron Metrology Offices

Addresses for Offices worldwide

United Kingdom - Head Office

Solartron Metrology
Steyning Way
Bognor Regis
West Sussex
PO22 9ST

Tel: +44 (0) 1243 833333
Fax: +44 (0) 1243 833332
sales.solartronmetrology@ametek.com

Germany
Ametek GmbH
Solartron Metrology Division
Rudolf-Diesel-Strasse 16
40670 Meerbusch

Tel: +49 (0) 2159 9136 500
Fax: +49 (0) 2159 9136 505
vertrieb.solartronmetrology@ametek.com

France
Solartron Metrology
Rond-point de l'Epine des Champs
Buroplus - Bat D
Elancourt, 78990

Tel: +33 (0)1 30 68 89 50
Fax: +33 (0)1 30 68 89 59
france.solartronmetrology@ametek.com

China - Shanghai
Solartron Metrology
Rm 912, Metro Tower
No 30 Tian Yao Qiao Road, Shanghai
200030

Tel: +86 21 6426 8111
Fax: +86 21 6426 7818
china.solartronmetrology@ametek.com

China - Beijing
Solartron Metrology
Room 2202, CITIC Building
#19, Jianguomenwai Dajie
Beijing
100004 P.R China

Tel: +86 10 8526 2111
Fax: +86 10 8526 2141
china.solartronmetrology@ametek.com

China - Chengdu
Solartron Metrology
AMETEK ChengDu Rep Office
Room 2408, Zongfu Building
35 Zongfu Road
Chengdu, Sichun, 610016, China

Tel: +86 28 8675 8111
Fax: +86 28 8675 8141
china.solartronmetrology@ametek.com

Japan
Solartron Metrology
4-5-37 Kamiosaki
Shinagawa-Ku
Tokyo
141-0021

Tel: +81(0) 3 3494 5131
Fax: +81 (0) 3 3494 5134
japan.solartronmetrology@ametek.com

U.S.A
Solartron Metrology
915 N.New Hope Road
Suite C, Gastonia
NC 28054, USA

Tel: +1 800 873 5838
Fax: +1 704 868 8466
usasales.solartronmetrology@ametek.com

Agent and Distributor details available at www.solartronmetrology.com

